

# 250 Jackleg

*The 250 Drills have larger mating faces between major cylinder components for reduced air leakage and longer wearing life.*

- ◆ All internal parts in the 250 Jacklegs are used in 250 Stoppers, Sinkers and Quarry drills.
- ◆ Drill delivers high penetration, and strong torque.
- ◆ Convenient operating controls, with push button leg retraction and adjustable motorcycle control feed on the backhead of the drill.
- ◆ Positive lubrication with strong front end blow.
- ◆ Larger mating faces between major cylinder components for longer life and less wear.
- ◆ Improved pusher leg is available with stainless steel piston rod to prevent corrosion and pitting.
- ◆ Locking steel retainer for collared steel standard.
- ◆ Uses rock drill oil or grease.
- ◆ Various airleg lengths available.



## Features

Large mating faces on components bodies for less wear and longer life.  
Reduced weight for ease of handling.

### Jackleg Configurations

- JHM Integral steel muffler
- JHS Standard Exhaust
- L Complete with Leg

Item	Specification
Cylinder Bore	3 1/8" (79.4 mm)
Cylinder Stroke	2 7/8" (73.25 mm)
Air Consumption	175cfm @ 90psi (4.9cu m/m @ 620kPa)
Blows Per Minute	2250bpm @ 90psi (2250bpm @ 620kPa)
Shank Size - Collared	7/8" x 4 1/4" (22mm x 108mm)
Length	Drill 27" (686mm); Leg Retracted 68" (1727mm) Leg Extended 119" (3033mm)
Weight	Drill 81lbs (32.7kg) Leg 35lbs (15.9kg)

Canyon carries a full range of parts for the 250 drills in stock. All parts are made in Canada to precise specifications using only the highest quality tool steel.